# ZIC

# **SK WHEEL BEARING GREASE 2**

Safety Data Sheet

### 1. Identification of Substance & Company

Product name Product code HSNO approval Approval description UN number Proper Shipping Name DG class Packaging group Hazchem code Uses Company Details Company Address

SK WHEEL BEARING GREASE 2 to be advised HSR002605 Lubricants (Low Hazard) Group Standard 2006 NA NA NA NA NA Grease

New World Motors Ltd PO Box 132316, Sylvia Park Auckland 1644

#### 2. Hazard Identification

Approval

This product has been approved under the Hazardous Substances and New Organisms Act (HSNO, Approval HSR002605, Lubricants (Low Hazard) Group Standard 2006), and is classified as follows:

Classes Hazard Statements

6.3B

6.4A

H316 - Causes mild skin irritation. H320 - Causes eye irritation.





Other Classifications There are no other Classifications that are known to apply. Precautionary Statements

Read label before use.

Wash hands thoroughly after handling.

Wear eye/face protection.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: get medical advice/attention. Take off contaminated clothing and wash before re-use.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Apply continuous irrigation with water for at least 15 minutes holding eyelids apart. If eye irritation persists: Get medical advice.

#### 3. Composition / Information on Ingredients

Component	CAS/ Identification	Conc (%)
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	32.0-50.0%
Distillates (petroleum), solvent-refined heavy naphthenic	64741-96-4	20.0-27.0%
Residual oils (petroleum), dewaxed	64742-62-7	20.0-27.0%
Octadecanoic acid, lithium salt	4485-12-5	9.0-12.0%
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	68649-42-3	1.0-2.0%

This is a commercial product whose exact ratio of components may vary. Trace quantities of impurities are also likely.

# 

## SK WHEEL BEARING GREASE 2 Safety Data Sheet

## 4. First Aid

General Information			
	If medical advice is needed, have product container or label at hand. You should call the National Poisons Centre if you feel		
	or irritated by this product. The number is 0800 764 766 (0800 POISON) (24 hr emergency		
service).			
Recommended first aid	Ready access to running water is recommended.		
facilities			
Exposure			
Swallowed Eye contact	Do NOT induce vomiting. Give a glass of water to drink. Contact a doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Apply continuous irrigation with water for at least 15 minutes		
	holding eyelids apart. If eye irritation persists: Get medical advice.		
Skin contact	IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: get medical advice/attention. Take off contaminated clothing and wash before re-use.		
Inhaled	Generally, inhalation of fumes is unlikely to result in adverse health effects. If coughing, dizziness or shortness of breath is experienced, remove the patient to fresh air immediately. If patient is unconscious, place in the recovery position (on the side) for transport and contact a doctor.		
Advice to Doctor			
Treat symptomatically			
Teat symptomatically			
5. Firefighting Measures			
Fire and explosion hazards:	There are no specific risks for fire/explosion for this chemical. It is non-flammable.		
Suitable extinguishing	Carbon dioxide, extinguishing powder or water jet. Fight larger fires with water jet or		
substances:	alcohol resistant foam.		
Unsuitable extinguishing	Unknown.		
substances:			
Products of combustion:	Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Water.		
	May form toxic mixtures in air and may accumulate in sumps, pits and other low-lying		
Desta sting a main mante	May form toxic mixtures in air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures.		
Protective equipment:	May form toxic mixtures in air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures. No special measures are required.		
Protective equipment: Hazchem code:	May form toxic mixtures in air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures.		
	May form toxic mixtures in air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures. No special measures are required. NA		
Hazchem code: 6. Accidental Releas	May form toxic mixtures in air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures. No special measures are required. NA		
Hazchem code:	May form toxic mixtures in air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures. No special measures are required. NA <b>Memory Measures</b> If greater than 10000L is stored, secondary containment and emergency plans to manage any potential spills must be in place. In all cases design storage to prevent		
Hazchem code: 6. Accidental Releas Containment	May form toxic mixtures in air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures. No special measures are required. NA <b>Memory Content of Secondary Containment and Emergency Plans to Memory Containment and Emergency Plans to Memor</b>		
Hazchem code: 6. Accidental Releas	May form toxic mixtures in air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures. No special measures are required. NA <b>Memory Measures</b> If greater than 10000L is stored, secondary containment and emergency plans to manage any potential spills must be in place. In all cases design storage to prevent		

**Clean-up method** 

Disposal

Precautions

### 7. Storage & Handling

StorageAvoid storage of harmful substances with food. Containers should be kept closed in<br/>order to minimise contamination. Keep from extreme heat and open flames. Avoid<br/>contact with incompatible substances as listed in Section 10.HandlingKeep exposure to a minimum, and minimise the quantities kept in work areas. See<br/>section 8 with regard to personal protective equipment requirements.

landfill. Dispose of only in accord with all regulations.

No special protective clothing is normally necessary.

and collected.

Stop leak if safe or necessary. Isolate area. Collect spill, see below. Transfer to container for disposal. Dispose of according to guidelines below (Section 13).

This product is not considered flammable or ecotoxic. Small spills do not require any special clean up method. Larger spills (e.g., greater than 10kg) should be mopped up

Mop up and collect recoverable material into labelled containers for recycling or salvage. Recycle containers wherever possible. This material may be suitable for approved

# ZIC

# **SK WHEEL BEARING GREASE 2**

Safety Data Sheet

#### 8. Exposure Controls / Personal Protective Equipment

#### Workplace Exposure Standards

A workplace exposure standard (WES) has not been established by WorkSafe NZ for this product. There is a general limit of 10mg/m<sup>3</sup> for dusts and mists when limits have not otherwise been established.

NZ Workplace	Ingredient	WES-TWA	WES-STEL
Exposure Stds	Oil mist, mineral	5mg/m <sup>3</sup>	10mg/m <sup>3</sup>
(2016)			

\* These workplace exposure standards are also Prescribed Exposure Standards (PES) under the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016.

#### Engineering Controls

In industrial situations, it is expected that employee exposure to hazardous substances will be controlled to a level as far below the WES as practicable by applying the hierarchy of control required by the Health and Safety at Work Act (2015) and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016. Exposure can be reduced by process modification, use of local exhaust ventilation, capturing substances at the source, or other methods. If you believe air borne concentrations of mists, dusts or vapours are high, you are advised to modify processes or increase ventilation.

### **Personal Protective Equipment**

Eyes



Protective eyewear is not normally necessary when using this product. However, it always prudent to use protective eyewear if splashes are likely or if handling material in bulk.

Skin

Respiratory

If discomfort is felt (e.g., if pre-existing conditions exist, such as dermatitis, cuts or sensitive skin), gloves may be helpful. If you suffer from dermatitis type skin conditions, use gloves. Nitrile or NBR gloves are recommended. Replace frequently. Gloves should be checked for tears or holes before use. A respirator when airborne concentrations approach the WES (section 8). Use an organic

vapour cartridge with a dust/mist filter'. If using a respirator, ensure that the cartridges are

correct for the potential air contamination and are in good working order.

WES Additional Information Not applicable

#### Physical & Chemical Properties

#### 10. Stability & Reactivity

avoid contamination. Keep from extreme
3

# ZIC

11. Toxicological Information

T1. Toxicological information				
	Summary			
	IF SWALLOWED: no known effect.			
	S: may be irritating.	ivitation		
	N: may cause mild skin	ibstance has a very low vapour pressure.		
	TOXICITY: no known e			
Supportin				
Acute	Oral	Using LD <sub>50</sub> 's for ingredients, the calculated LD <sub>50</sub> (oral, rat) for the mixture is $>5,000$		
		mg/kg. Data considered includes: Distillates (petroleum), solvent-dewaxed heavy		
		paraffinic >5000mg/kg bw (rat), Distillates (petroleum), solvent-refined heavy naphthenic		
	Dermal	>15g/kg (rat).		
	Dermai	Using LD <sub>50</sub> 's for ingredients, the calculated LD <sub>50</sub> (dermal, rat) for the mixture is $>5000$ mg/kg. Data considered includes: Distillates (petroleum), solvent-dewaxed heavy		
		paraffinic >2000mg/kg be (rabbit), Distillates (petroleum), solvent dewaxed neavy		
		naphthenic >5g/kg (rabbit).		
	Inhaled	Using LC <sub>50</sub> 's for ingredients, the calculated LC <sub>50</sub> (inhalation, rat) for the mixture is		
		>5mg/L. Data considered includes: Distillates (petroleum), solvent-dewaxed heavy		
	Eye	paraffinic >5.53mg/L (rat). The mixture is considered to be an eye irritant, because some of the ingredients present		
	_,.	are considered eye irritants in more concentrated form.		
	Skin	The mixture is considered to be a skin irritant, because some of the ingredients present		
<b>.</b>	•	are considered skin irritants in more concentrated form.		
Chronic	Sensitisation Mutagenicity	No ingredient present at concentrations > 0.1% is considered a sensitizer. No ingredient present at concentrations > 0.1% is considered a mutagen.		
	Carcinogenicity	No ingredient present at concentrations > 0.1% is considered a mutagen.		
	Reproductive /	No ingredient present at concentrations > 0.1% is considered a reproductive or		
	Developmental	developmental toxicant or have any effects on or via lactation.		
	Systemic	No ingredient present at concentrations > 1% is considered a target organ toxicant.		
	Aggravation of existing conditions	None known.		
	existing conditions			
12. Ecological Data				
	loologioal Bata			
Summary				
Highly refined base oil have a very low toxicity towards aquatic organisms. May cause physical fouling of aquatic organisms.				
Supportin	g Data			
Aquatic		Using EC <sub>50</sub> 's for ingredients, the calculated EC <sub>50</sub> for the mixture is $> 100 \text{ mg/L}$ . Data		
Bioaccum	ulation	considered includes: Distillates (petroleum), solvent-refined heavy naphthenic >100mg/L. May be bioaccumulative.		
Degradab		Not considered degradable, but will biodegrade. Petroleum distillates: log Kow 3.9 ~ 6		
-		(estimate)		
Soil		No evidence of soil toxicity.		
	l vertebrate I invertebrate	Not considered ecotoxic towards terrestrial vertebrates (see acute toxicity)		
Biocidal		No evidence of toxicity towards terrestrial invertebrates. no data		
	ental effect levels	No EELs are available for this mixture or ingredients		
		-		

## 13. Disposal Considerations

Restrictions	There are no product-specific restrictions, however, local council and resource consent conditions may apply, including requirements of trade waste consents. Disposal of this product must comply with the requirements of the Resource Management Act for which approval should be sought from the Regional Authority. The substance must be treated and therefore rendered non-hazardous before discharge to the environment.	
Disposal method		
Contaminated packaging	Rinse containers with water before disposal. Preferably re-cycle container, otherwise send to landfill or similar.	

14. Transport	Information		
There are no specific restrictions for this product (not a dangerous good).			
UN number:	NA	Proper shipping name:	NA
Class(es)	NA	Packing group:	NA
Precautions:	Not applicable.	Hazchem code:	NA



# **SK WHEEL BEARING GREASE 2**

**Safety Data Sheet** 

## 15. Regulatory Information

This product is an approved substance under the Hazardous Substances and New Organisms Act (HSNO). Approval code: HSR002605, Lubricants (Low Hazard) Group Standard 2006.

Specific Workplace Controls (as per HSNO approval referenced to Controls Matrix)

	Key workplace requirements are:	
SDS		To be available within 10 minutes in workplaces storing > 50L.
	Labelling	No removal of labels and/or decanting of product into other containers can occur.
	Emergency plan	Required if > 10000L is stored.
	Approved handler	Not required.
	Tracking	Not required.
	Bunding & secondary containment	Required if > 10000L is stored.
	Signage	Required if > 10000L is stored.
	Location test certificate	Not required.
	Flammable zone	Not required.
	Fire extinguisher	Not required.

Note: The above workplace requirements apply if only this particular substance is present. The complete set of controls for a location will depend on the classification and total quantities of other substances present in that location. Other Legislation

In New Zealand, the use of this product may come under the Resource Management Act and Regulations, the Health and Safety at Work Act 2015 and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016, local Council Rules and Regional Council Plans.

## 16. Other Information

Abbreviations	
Approval Code	Approval HSR002605, Lubricants (Low Hazard) Group Standard 2006 Controls, EPA. www.epa.govt.nz
CAS Number Ceiling	Unique Chemical Abstracts Service Registry Number Ceiling Exposure Value: The maximum airborne concentration of a biological or chemical agent to which a worker may be exposed at any time.
Controls Matrix EC <sub>50</sub>	List of default controls linking regulation numbers to Matrix code (e.g. T1, I16). Ecotoxic Concentration 50% – concentration in water which is fatal to 50% of a test population (e.g. daphnia, fish species)
EPA HAZCHEM Code	Environmental Protection Authority (New Zealand) Emergency action code of numbers and letters that provide information to emergency services, especially fire fighters
HSNO	Hazardous Substances and New Organisms (Act and Regulations)
IARC	International Agency for Research on Cancer
LEL LD50	Lower Explosive Limit
LC <sub>50</sub>	Lethal Dose 50% – dose which is fatal to 50% of a test population (usually rats). Lethal Concentration 50% – concentration in air which is fatal to 50% of a test population (usually rats)
MSDS (SDS)	Material Safety Data Sheet (or Safety Data Sheet)
PES	Prescribed Exposure Standard means a WES or a biological exposure standard that is prescribed in a regulation, a safe work instrument or an approval under HSNO (including group standards).
STEL	Short Term Exposure Limit - The maximum airborne concentration of a chemical or biological agent to which a worker may be exposed in any 15 minute period, provided the TWA is not exceeded
TWA	Time Weighted Average – generally referred to WES averaged over typical work day (usually 8 hours)
UEL UN Number WES	Upper Explosive Limit United Nations Number Workplace Exposure Standard - The airborne concentration of a biological or chemical agent to which a worker may be exposed during work hours (usually 8 hours, 5 days a week). The WES relates to exposure that has been measured by personal monitoring using procedures that gather air samples in the worker's breathing zone.



# **SK WHEEL BEARING GREASE 2**

**Safety Data Sheet** 

References	
Data	Unless otherwise stated comes from the EPA HSNO chemical classification information database (CCID).
EPA Transfer Gazettes	Classifications and controls assigned for specific ingredients (consolidated gazette, 2004)
WES 2013	The NZ Workplace Exposure Standards Effective from 2013, published by WorkSafe NZ and available on their web site – www.worksafe.govt.nz.
WES 2002	Workplace Exposure Standards published by the Occupational Safety and Health Service, Department of Labour, January 2002, ISBN 0-477-03660-0. These are the WES referred to under the Group Standard (HSNO approval) and may constitute a PES.
Other References:	Suppliers SDS
Review	
Date	Reason for review
October 2016	Not applicable – new SDS

#### Disclaimer

This SDS was prepared by Datachem LTD and is based on our current state of knowledge, including information obtained from suppliers. The SDS is given in good faith and constitutes a guideline (not a guarantee of safety). The level of risk each substance poses is relevant to its properties (as summarised in the SDS) AND HOW THE SUBSTANCE IS USED. While guidelines are given for personal protective equipment, such precautions must be relevant to the use. The likely HSNO classifications for this SDS have been estimated based on general information from the supplier (e.g., hazard, toxicological). This SDS is copyright Datachem and must not be copied, edited or used for other than intended purpose. To contact the SDS author, email info@datachem.co.nz or phone: +64 9 940 30 80.

